Produkte
Mainboard Serie
»FM2A88M Extreme4+
»Überblick
»Spezifikationen
»Download
»Handbuch
»FAQ
»CPU Support Liste
»Speicher Support Liste

ASRock Channel on YouTube
facebook Follow ASRock on facebook now!
ASRock Forum
A-STYLE Your Lifestyle
Home Cloud
FM2 X-Boost
FATAL1TY Gaming Motherboard series

FM2A88M Extreme4+

Translate

- A-Style : Home Cloud
- Supports Socket FM2+ 95W / FM2 100W processors
- All Solid Capacitor Design
- Supports Dual Channel DDR3 2600+(OC)
- 1 x PCIe 3.0 x16, 1 x PCIe 2.0 x16, 1 x PCIe 2.0 x1, 1 x PCI
- Supports AMD Quad CrossFireX™, CrossFireX™ and Dual Graphics
- Integrated AMD Radeon HD 8000/7000 series graphics in A-series APU
- Multi VGA Output Options : D-Sub, DVI-D, HDMI
- 7.1 CH HD Audio with Content Protection (Realtek ALC892 Audio Codec)
- 8 x SATA3, 4 x USB 3.0 (2 Front, 2 Rear), 10 x USB 2.0
- Supports A-Tuning, XFast 555, X-Boost, Easy Driver Installer, FAN-Tastic Tuning, USB Key

Windows 8 Ready

Dieses Modell wird nicht in allen Regionen der Welt verkauft. Bezüglich der Verfügbarkeit in Ihrer Region kontaktieren Sie bitte Ihren Händler.

Produkt Spezifikationen

Generelles	
A-Style	- Home Cloud
CPU	- Supports Socket FM2+ 95W / FM2 100W processors - 4 + 2 Power Phase design
Chipsatz	- AMD A88X (Bolton-D4)
Arbeitsspeicher	- Dual Channel DDR3 Memory Technology - 4 x DDR3 DIMM Slots - Supports DDR3 2600+(OC)*/2400(OC)/2133/1866/1600/1333/1066 non-ECC, un-buffered memory - Max. capacity of system memory: 64GB** - Supports Intel® Extreme Memory Profile (XMP) 1.3 / 1.2 - Supports AMD Memory Profile (AMP) *DDR3 2600+ is only supported with two DIMMs. **Due to the operating system limitation, the actual memory size may be less than 4GB for the reservation for system usage under Windows® 32-bit OS. For Windows® 64-bit OS with 64-bit CPU, there is no such limitation.
BIOS	- 64Mb AMI UEFI Legal BIOS with GUI support - Supports "Plug and Play" - ACPI 1.1 Compliant wake up events - Supports jumperfree - SMBIOS 2.3.1 support - DRAM, CPU Voltage multi-adjustment
Audio, Video und Netzwerk	
Grafik	- Integrated AMD Radeon HD 8000/7000 series graphics in A-series APU - DirectX 11.1, Pixel Shader 5.6 with FM2+ CPU. DirectX 11, Pixel Shader 5.0 with FM2 CPU. - Max. shared memory 2GB - Multi VGA Output options: D-Sub, DVI-D and HDMI Ports - Supports Triple Monitor - Supports HDMI Technology with max. resolution up to 1920x1200 @ 60Hz - Supports Dual-link DVI-D with max. resolution up to 2560x1600 @ 60Hz - Supports D-Sub with max. resolution up to 1920x1200 @ 60Hz - Supports Auto Lip Sync, Deep Color (12bpc), xvYCC and HBR (High Bit Rate Audio) with HDMI Port (Compliant HDMI monitor is required) - Supports Blu-ray Stereoscopic 3D with HDMI Port - Supports AMD Steady Video™ 2.0: New video post processing capability for automatic jitter reduction on home/online video - Supports HDCP with DVI-D and HDMI Ports - Supports Full HD 1080p Blu-ray (BD) playback with DVI-D and HDMI Ports
Audio	- 7.1 CH HD Audio with Content Protection (Realtek ALC892 Audio Codec) - Premium Blu-ray Audio support
LAN	- PCIE x1 Gigabit LAN 10/100/1000 Mb/s - Qualcomm Atheros AR8171 - Supports Qualcomm Atheros Security Wake On Internet Technology - Supports Wake-On-LAN - Supports Energy Efficient Ethernet 802.3az - Supports PXE
Erweiterungsslots/Konnektivität	
Steckplätze	- 1 x PCI Express 3.0 x16 Slot (PCIE1 @ x16 mode) - 1 x PCI Express 2.0 x16 Slot (PCIE3 @ x4 mode) - 1 x PCI Express 2.0 x1 Slot - 1 x PCI Slot - Supports AMD Quad CrossFireX™, CrossFireX™ and Dual Graphics *PCIE 3.0 is only supported with FM2+ CPU. With FM2 CPU, it only supports PCIE 2.0.
Opslagruimte	- 8 x SATA3 6.0 Gb/s Connectors, support RAID (RAID 0, RAID 1, RAID 5 and RAID 10), NCQ, AHCI and Hot Plug
Anschluss	- 1 x IR Header - 1 x Print Port Header - 1 x COM Port Header - 1 x Chassis Intrusion Header - 1 x TPM Header - 1 x Power LED Header - 2 x CPU Fan Connectors (1 x 4-pin, 1 x 3-pin) - 1 x Chassis Fan Connector (4-pin) - 1 x Power Fan Connector (3-pin) - 1 x 24 pin ATX Power Connector - 1 x 8 pin 12V Power Connector - 1 x Front Panel Audio Connector - 3 x USB 2.0 Headers (Support 6 USB 2.0 ports)

	- 1 x USB 3.0 Header by AMD A88X (Bolton-D4) (Supports 2 USB 3.0 ports)
ATX-Blende	- 1 x PS/2 Mouse/Keyboard Port - 1 x D-Sub Port - 1 x DVI-D Port - 1 x HDMI Port - 1 x Optical SPDIF Out Port - 4 x USB 2.0 Ports - 2 x USB 3.0 Ports (AMD A88X (Bolton-D4)) - 1 x RJ-45 LAN Port with LED (ACT/LINK LED and SPEED LED) - HD Audio Jacks: Rear Speaker / Central / Bass / Line in / Front Speaker / Microphone
Sonstige Features/Verschiedenes	
Einzigartige Features	- ASRock A-Tuning - ASRock Instant Boot - ASRock Instant Flash - ASRock APP Charger - ASRock XFast USB - ASRock XFast LAN - ASRock XFast RAM - ASRock Crashless BIOS - ASRock OMG (Online Management Guard) - ASRock Internet Flash - ASRock UEFI System Browser - ASRock UEFI Tech Service - ASRock On/Off Play Technology - ASRock Dehumidifier Function - ASRock Easy RAID Installer - ASRock Easy Driver Installer - ASRock Interactive UEFI - ASRock Fast Boot - ASRock X-Boost - ASRock Restart to UEFI - ASRock USB Key - ASRock FAN-Tastic Tuning - Hybrid Booster: - ASRock U-COP
Support-CD	- Drivers, Utilities, AntiVirus Software (Trial Version), CyberLink MediaEspresso 6.5 Trial, Google Chrome Browser and Toolbar, Start8 (30 days trial)
Produktzubehör	- Quick Installation Guide, Support CD, I/O Shield - 2 x SATA Data Cables
Hardware überwachung	- CPU temperature sensing - Chassis temperature sensing - CPU Fan Tachometer - Chassis Fan Tachometer - CPU/Chassis Quiet Fan - CPU/Chassis Fan multi-speed control - CASE OPEN detection - Voltage monitoring: +12V, +5V, +3.3V, Vcore
Formfaktor	- Micro ATX Form Factor - All Solid Capacitor design
Betriebssystem	- Microsoft® Windows® 8.1 32-bit / 8.1 64-bit / 8 32-bit / 8 64-bit / 7 32-bit / 7 64-bit / XP 32-bit
Zertifizierungen	- FCC, CE, WHQL - ErP/EuP ready (ErP/EuP ready power supply is required)

Achtung:
Bitte beachten Sie, dass Overclocking, inklusive dem Verändern von BIOS-Einstellungen und der Nutzung von Overclockingprogrammen von Drittherstellern, immer ein gewisses Risiko bürgt. Overclocking kann ihre Systemstabilität beeinflussen oder aber zu Schäden Ihrer Komponenten und Geräte führen. Die Ausführung geschieht auf eigene Gefahr und Kosten. Für Schäden die durch Overclocking verursachet werden sind wir nicht verantwortlich.

Die Spezifikationen können ohne vorherigen Hinweis geändert werden. Die Marken und Produktnamen sind Schutzmarken der jeweiligen Firmen. Alle Konfigurationen die von den original Spezifikationen abweichen werden nicht garantiert.

© 2002-2013 ASRock Inc Alle Rechte vorbehalten | Informationen die auf asrock.com veröffentlicht werden, können ohne Hinweis geändert werden.
Das oben abgebildete User-Interface ist ein Referenzbeispiel. Das tatsächliche User-Interface kann von der Abbildung abweichen.